HD PTZ Wireless Day/Night Cloud Camera

C50s HD PTZ IP-Camera provides a professional home or small business day-and-night surveillance solution. Coming with the latest technology of security monitoring, C50s features itself with 720P HD lens with 11-metre IR-LED illumination distance. It serves as a warden for your family, office or warehouse, and protects your house from theft and burgling. In addition, the easy-installed app “TendaViewer” allows the user to receive alarming notification on your mobile devices.

C50s

Home security in high definition

C50s HD video gives you a clear view of what's going on at home. See more of your faces and places - it's home security with an eye for detail.

Motion Detection & Notification/Image Push

When detecting motions, the camera automatically triggers alert and takes a snapshot.
Notification Push: the information of the alert can be pushed to you on the phone as soon as the alert is triggered.
Image Push: the snapshot of the alert can be sent to your phone so that you can see the details.

SD/TF Card Storage

The recorded video can be stored in the SD/TF card, which can be plugged in the external TF card slot. C50s allows a maximum of 64GB TF card storage. And a 64GB card can save the video for about 400 hours. You just need to click the “record” button and you’ll see the video recorded in the SD card.

Easy to Set up

No matter you are a tech-savvy enthusiast or a newbie, Wi-Fi smart config helps you connect the camera to the Internet effortlessly in 30 seconds, and place it just about anywhere in your home.

Features

- ●High Definition Surveillance
- ●Pan/tilt
- ●Two-way Audio
- ●Night Vision(IR LEDS)
- ●Audio Detection Alerting

Setting

●Indoor

System Requirements

●Android 4.2,iOS7.0 above

Supported Mobile Devices

●TendaViewer app for iPhone, iPad, and Android mobile devices

Specification

Image Sensor	
•1/4" Megapixel color CMOS sensor	
•Built-in Infrared-Cut Removable (ICR) Filter module	
•Lens,f=3.6mm F=2.0 Angle of view: D=68°(Pan/Tilt Angle:	
•10-meter night vision with 11 infrared LEDs	
•Minimum illunimation: 0 lux with IR-LEDs on	
Video Features	
•Configurable image size, quality, frame rate, and bit rate	
•Time stamp and text overlays	
•Configurable brightness, saturation, contrast, mirror, flip	
Video Compression	
•H.264/MJPEG format simultaneous compression	
•H.264 multicast streaming	
•JPEG for still images	
Video Resolution	
•1280*720 (HD) ; 640*480 (VGA) ; 320*240 (QVGA)	
Pan/Tilt/Zoom	
•Pan range: 355° ; Tilt range : 120° ; Pre-set setting : 6 points ; Zoom : digital 5x	
Audio	
•Audio Compression ADPCM	
•Built-in microphone and speaker	
Network Protocol Support	
•TCP/IP,UDP,ARP,ICMP,DHCP client,NTP client, DNS client, DDNS client, SMTP client, FTP client, HTTP, RTP / RTSP/ RTCP, ONVIF compliant	
Network Interface	
•IEEE 802.11n/g/b,2.4G,150Mbps	
Security	
•Administrator , operator and user group protected	
•Password authentication	
•HTTP and RTSP authentication	
Surveillance	
•Record video continuously	
•Record video according to a weekly schedule	
•Record video when motion is detected	
•Record video when sound is detected	
•Upload snapshots via e-mail	
•Upload snapshots via FTP	
Certifications	
•CE 、CE LVD 、RoHs、FCC Class B 、BSMI/NCC	
Physical	
Dimensions	•118*107*106mm(L*W*H)
Net Weight	•0.316Kg
Power Input	•Input: 9V DC, 1A
Temperature	•Operating: -10 to 50 °C
	•Storage: -40 to 70 °C
Humidity	•Operating: 10% to 80% non-

Shenzhen Tenda Technology Co., Ltd.
6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road,
Nanshan District, Shenzhen,China. 518052
Phone : (86 755)86591006
Fax : (86 755)26757178
Email : IPC@tenda.com.cn
Website: http://www.tendacn.com

Specifications are subject to change without notice. Tenda is a registered trademark legally held by Shenzhen Tenda Technology Co., Ltd. Other brand and product names mentioned herein are trademarks or registered trademarks of their respective holders.
Copyright © 2016 Shenzhen Tenda Technology Co., Ltd. All rights reserved.