D305

4 Antennas Wireless N300 ADSL2+ Modem Router


Tenda D305 combines the function of 300Mbps wireless router , ADSL2+ Modem in one device to provide one-stop networking solution. With external 4*5dBi high gain omnidirectional antennas with external PA, D305 can provide ultimate WiFi coverage for large house. LNA design and WPA2-PSK high level encryption mechanism ensure stable and secure WiFi experience. Additionally, D305 can detect phone cable , ethernet cable access mode and PVC automatically to provide quick & hassle-free installation. You can enjoy the pleasant of Internet surfing, file sharing, VoIP, audio and Video streaming using one device instead of multiple devices to save time, money and space.





Simple & Perfect Connection

Combines the function of ADSL2+ WiFi Router, Superior WiFi can satisfy phone cable & broadband access needs. Surfing is so easy!



All-in-One Device for Multiple Connections

300Mbps ADSL2+ WiFi Router, ideal for multiple HD video streams, wholehome coverage with different connections



Whole-home WiFi Coverage

4*5dbi external antennas ,PA & LNA helps you keep mobile devices,media players and computers connected to WiFi in each corner of your house. No longer need to worry about the WiFi deadzones.



Smart Access for All Connections

Distinguishes your existing access modes automatically and with the intuitive user interface, you can connect Internet easily.




Compatible with Global ISP

With PVC detect technology to recognize correct parameters automatically, D305 is compatible with global ISP.

Tenda

- 4*5dBi external antennas with external PA and internal LNA bring ultimate WiFi coverage and stable WiFi experience.
- Detect phone cable , ethernet cable access mode and PVC automatically to provide quick & hassle-free installation.
- Turn on/off WiFi switch to create low-power consumption and smart E-life for your whole families.
 Up to 6000V lightning protection prolongs router lifespan.
- Supports bandwidth control, WDS, TR069, virtual server and web filter etc.



Specifications

Hardware Features	
	IEEE 802.3, 802.3u
	Full-rate ANSI T1.413 Issue 2
Protocols	ITU-T G.992.1 (G.dmt)
&	ITU-T G.992.2 (G.lite)
Standards	ITU-T G.994.1 (G.hs)
	ITU-T G.992.3 (G.dmt.bis) Annex A/L/M
	ITU-T G.992.5 Annex A
Interface	RJ11 × 1
	Power Jack × 1
	USB2.0 × 1
	10/100Mbps LAN × 3
	10/100Mbps WAN × 1
Antenna	5dBi External Omni directional × 4
Button	WLAN ON/OFF
	RST/WPS
	Power
Power Adapter	Input: 100 - 240V 50/60Hz
	Output: 12V1A
Dimensions	190 × 125 × 26.5mm
LEDs	Power, SYS, Internet, USB, WPS, WLAN, LAN(1,2,3,4), DSL
Wireless Features	
Wireless Rate	300Mbps
Frequency	2.4GHz
Basic Features	Wireless ON/OFF
	SSID Broadcast ON/OFF
	RF Power Setting Normal/Enhanced
	Country Options
	Channel: Auto, 1-13
	Bandwidth: Auto, 20MHz, 40MHz
	Client List
	WDS
Wireless Security	Wireless MAC Filtering
	Support 64/128 bit WEP
	WPA-PSK/WPA2-PSK
	WPS



Coffeen Footons	
Software Features	Description Continue DDD F DDD A ID A Dide
Connection Type	Dynamic IP、Static IP、PPPoE、PPPoA、IPoA、Bridge
Operating Mode	ADSL2+ Modem Router, Wireless Router
Advanced Feature	PVC Configuration
	MAC Clone
	DSL Settings
	Interface Grouping
DHCP	QoS(Based IP)
	DHCP Server
	Client List
	Address Reservation
Virtual Server	Port Forwarding
	Port Triggering
	DMZ
	UPnP
Security	IP, MAC Filtering
Ipv6 Tunnel	Support 6RD & DS-Lite, IPv6 and IPv4 dual stack
	LAN IP Setting
	System Log
	Device Info
	Remote Management
Device	Internet Time
Management	Backup & Restore Backup
	Restore Default
	Diagnostic Tools
	Web Based Firmware Upgrade
	Access Control
Others	DDNS、IGMP Multicast、TR069
Others	
	Operating Temperature: 0°C ~ 40°C
Temperature	Storage Temperature: -40°C~70°C
Humidity	Operating Humidity: 10% ~ 90%RH non-condensing
	Storage Humidity: 5% ~ 90%RH non-condensing
Defaul Settings	IP Address: 192.168.1.1
	Login Username: admin Login Password: admin
Certificates	CE、FCC、RoHS
Related Products	UH150 High Power Wireless N150 USB Adapter
	W522U 300Mbps Dual Band Wireless N USB Adapter
	DH301 Wireless N300 ADSL2+ High Power Modem Router
Package Contents	D305 4 antennas Wireless N300 ADSL2+ Modem Router × 1
	Quick Installation Guide x 1
	Power Adapter x 1
	Ethernet cable (RJ45) x 1
	Telephone cable (RJ11) × 2
	ADSL Splitter x 1
	·



SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int IE-City, #1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China. Tel:+86-755-2765 7098 E. Fax:+86-755-2765 7178 P.

E-mail:support@tenda.com.cn

PC:518055

Specifications are subject to change without notice. Copyright © 2015 SHENZHEN TENDA TECHNOLOGY CO., LTD. All rights reserved. Tenda is the trademark of SHENZHEN TENDA TECHNOLOGY CO., LTD. All other brand names mentioned herein are the trademark or registered trademarks of their respective holders.